CLEAN

TECHNICAL DATA SHEET

autoTAK®

D3035R

LIGHT TACK (HIGH QUALITY POLYESTER)



DESCRIPTION

autoTAK® is based on a specially selected, white high quality / high strength, continuous filament honeycomb knit polyester substrate impregnated with a non-drying resin.

Specifically designed to remove and collect dust, dirt, fibres, hair etc from prepared surfaces prior to finishing, painting or enhancement.

autoTAK® is impregnated to the optimum weight ratio with a unique resin system to provide extremely high absorbency and containment retention

FEATURES & BENEFITS

The continuous filament polyester fabric used in **autoTAK®** provides strong, tear resistance whilst also ensuring high dirt absorbency to maximise dirt retention. The specially formulated tack resin maximises dirt pick-up whilst preventing possible resin transfer, whilst also ensuring that the Gramos® TAKrags® will not dry out.

autoTAK® is for use where all types of paint systems are employed and is particularly effective with the premium paint finish demanded by automotive manufacturers.

CHARACTERISTICS

Fabric:	Continuous Knitted Polyester	**Size:**	20 x 50cm
Colour:	White	**Tack Level:**	Light Tack

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.

ORAPI MAINTENANCE UK Ltd, Unit 8, Britannia Park, Patent Drive,
Wednesbury, West Midlands, WS10 7XD

Tel: +44 121 525 4000 Web: www.orapi.uk Email: info.uk@orapi.com

CLEAN

TECHNICAL DATA SHEET

STORAGE

Store in a dry place at ambient temperatures.

DIRECTIONS FOR USE

Minimal pressure should be applied, simply lightly wipe the surface to remove loose particles of contamination, and leave surface free of dust, lint/fibre and dirt. Turn the cloth regularly to expose a clean surface and wipe until surface soiling is removed. Re-seal pack when done to prevent contamination.

HEALTH & SAFETY

Gramos® TAKrags® are not classified as hazardous products.

Refer to Material Safety Data Sheet for further information.

PACKAGING

D3035R-10x50	Bulk pack

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.

ORAPI MAINTENANCE UK Ltd, Unit 8, Britannia Park, Patent Drive,
Wednesbury, West Midlands, WS10 7XD

Tel: +44 121 525 4000 Web: www.orapi.uk Email: info.uk@orapi.com