PROTECT

TECHNICAL DATA SHEET

AQUAPEEL TS

D4608

WATER-BORNE PEELABLE COATING (TRANSPARENT)



DESCRIPTION

Aquapeel TS is a water-based, transparent, temporary protective coating designed for application to glass, light fittings and other surfaces that require good through visibility. This peelable coating provides an easy method of maintenance as the dried film collects paint over-spray and is then readily peelable enabling over-spray deposits to be quickly and cleanly removed.

FEATURES & BENEFITS

- Easily peelable film.
- Enables overspray to be removed quickly and cleanly.
- Transparent surface for covering glass or light fittings.
- Reduces maintenance time.

CHARACTERISTICS

Appearance:	Colourless liquid	pH:	5.5 – 6.5
Odour:	No characteristic odour	Flash point:	Non-flammable
Base:	Polymer	Coverage:	5m^2 / L
Carrier:	Water	Drying time:	3 – 4 hrs (@20°C)
SG (@20°C):	1.04		

STORAGE

Store at ambient temperatures and protect from freezing.

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.

ORAPI MAINTENANCE UK Ltd, Unit 8, Britannia Park, Patent Drive,
Wednesbury, West Midlands, WS10 7XD

Tel: +44 121 525 4000 Web: www.orapi.uk Email: info.uk@orapi.com

PROTECT

TECHNICAL DATA SHEET

DIRECTIONS FOR USE

Best applied by roller to give 0.06-0.08 mm dry film thickness to achieve easy peelability from all smooth glass surfaces.
Do not thin prior to use.
May be applied to some painted and plastic surfaces also.

HEALTH & SAFETY

A non-hazardous product with no VOC's.
Refer to Material Safety Data Sheet for further information.

PACKAGING

D4608-25 25L Drum

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.

ORAPI MAINTENANCE UK Ltd, Unit 8, Britannia Park, Patent Drive,
Wednesbury, West Midlands, WS10 7XD

Tel: +44 121 525 4000 Web: www.orapi.uk Email: info.uk@orapi.com