CLEAN

ORAPI MAINTENANCE

TECHNICAL DATA SHEET

Pronatur Odourless Solvent

SLO6

Degreasing & Cleaning Solvent

DESCRIPTION

Pronatur Odourless Solvent is a high performance cleaning and degreasing solvents designed for use in heavy duty industrial cleaning applications. It has been formulated using a sophisticated blend of non-flammable solvents and cleaning agents that provide excellent cleaning and degreasing performance. The powerful formulation offers superior penetration of difficult to remove contaminants including mineral oils, greases, semi-cured adhesives and sealants, uncured paints, varnishes, and oil based inks making it a valuable addition to all workshops and maintenance areas.

Pronatur Odourless Solvent is a versatile product and is compatible with a range of cleaning equipment. The high flash point solvent blend is ideal for use in recirculating parts washers and ultrasonic baths where fluid loss through evaporation is kept to a minimum. The solvent based formulation is non miscible but is water washable, allowing for quick rinsing and eliminating any potential for tainting. This also makes it suitable for use with oil / water separation equipment allowing users to reduce wastage and minimise disposal costs.

Pronatur Odourless Solvent is compatible with all metals and alloys. It is not suitable for prolonged use on all plastics or painted surfaces which may undergo chemical attack on contact.

FEATURES & BENEFITS

- High performance cleaning solvent
- Low odour formulation
- Free from chlorinated solvents
- Non-flammable / high flashpoint formulation
- Non miscible / water rinseable formulation
- Easily cleans difficult to remove contaminants
- No unpleasant solvent odours
- Safe to use
- Reduces solvent loss due to evaporation
- Compatible with oil / water separation equipment

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.

ORAPI MAINTENANCE UK Ltd, Unit 8, Britannia Park, Patent Drive,
Wednesbury, West Midlands, WS10 7XD

Tel: +44 121 525 4000 Web: www.orapi.uk Email: info.uk@orapi.com

ORAPI MAINTENANCE

CLEAN

TECHNICAL DATA SHEET

CHARACTERISTICS

Appearance:	Clear colourless liquid	**Autoignition Temp:**	>250°C
Specific Gravity (20°C):	0.870 – 0.900 g/cm³	**Dielectric Strength:**	50kV
Flash Point:	98°C	**Evaporation Rate:**	0.06 (Water = 1)
Boiling Point:	199°C	**Solubility:**	Insoluble

STORAGE

Store in original containers away from direct sunlight. Protect from freezing.

DIRECTIONS FOR USE

Pronatur Odourless Solvent is supplied ready to use and should be used without dilution. It can be applied manually by wipe, brush or sponge or other suitable application equipment. It is suitable for use in spraywash systems and most common immersion cleaning systems including ultrasonic baths, recirculating parts washers, and immersion tanks.

For manual cleaning apply directly to areas of contamination by trigger spray or wipe. Wait a few seconds for the solvents to penetrate and wipe away with a clean cloth. For areas with heavy contamination re-apply as needed.

When using immersion tanks, ultrasonic baths, or parts washers the product should be added directly to the bath. Submerge parts and allow to stand. For heavy contamination some manual cleaning may be required. Once clean remove parts from solution and rinse with fresh water. Where suitable oil / water separation equipment is available clean parts as described above, once complete allow the bath to stand and allow phase separation to occur. Remove contaminated solvent as required.

HEALTH & SAFETY

Refer to separate Material Safety Data Sheet (MSDS) for further information.

PACKAGING

SLO620	6 x 1 litre	Bottles
SLO628	4 x 5 litres	Bottles
SLO632	1 x 25 litres	Drum

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.

ORAPI MAINTENANCE UK Ltd, Unit 8, Britannia Park, Patent Drive,
Wednesbury, West Midlands, WS10 7XD

Tel: +44 121 525 4000 Web: www.orapi.uk Email: info.uk@orapi.com